

# **Specification Sheet**

Part Number: 596-00672



Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", VL, Yellow, 10/pkg

Article Number	596-00672
Туре	CSESC10
Color	Yellow (YE)
Features & Benefits	<ul> <li>Made with UV stable inks and materials for durability and weather resistance.</li> <li>The labels are supplied with aggresive adhesive to ensure long life.</li> <li>Solar Installation labels meet NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li> </ul>
Quantity Per	pack

#### **Product Description**

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

# **Short Description**

Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", VL, Yellow, 10/pkg

**Global Part Name** 

CSESC10-242/552-YE

**Technical Description** 

Solar Label, Caution - Solar Electric System Connected Reflective Label, 6.5" X 1.0", Yellow

**Local Order Number 2** 

Cross Reference = 50 per roll: 596-00613; Spanish version 50 per roll: 596-00821

1000 141			
Width	w	(Imi	nerial)

6.5

#### Width W (Metric)

165.1

### Thickness T (Metric)

64.0

## Height H (Imperial)

1.0

#### **Height H (Metric)**

25.40

#### Material

Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

#### **Material Shortcut**

Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2014
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	.104
Weight (Imperial)	0.23

